



Main

Device short name	EGX100
Product or component type	Gateway module
Device application	Gateway
Range compatibility	Compact Masterpact PowerPact

Complementary

Communication network type	RS232/485, Modbus RTU and ASCII even/odd or none parity, at 38400/57600 bauds on SUB-D 9 RS232/485, PowerLogic (SY/MAX) even/odd or none parity, at 38400/57600 bauds on SUB-D 9 RS232/485, JBUS even/odd or none parity, at 38400/57600 bauds on SUB-D 9 Ethernet, HTTP on RJ45 Ethernet, Modbus TCP/IP on RJ45 Ethernet, FTP on RJ45 Ethernet, SNMP on RJ45
Communication gateway	Ethernet/Fieldbus
Mounting mode	By clips
Mounting support	35 mm DIN rail
Control type	By software
[Us] rated supply voltage	24 V DC
Power consumption in W	4 W
Product certifications	UL 508 CUL FCC Class A
Standards	EN 55011 EN 61000-4-8 AS/NZS 60950 EN 61000-4-2 EN 61000-4-5 EN 61000-6-2 UL 60950 EN/IEC 60950 EN 61000-4-3 EN 61000-4-4 EN 55022

EN 61000-4-6

Height	80.8 mm
Width	72 mm
Depth	65.8 mm
Product weight	0.17 kg
Language	French English Spanish German

Environment

IP degree of protection	IP30
Relative humidity	5...95 % at 55 °C without condensation
Ambient air temperature for operation	-25...70 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------